



xDSL Transformer

- Designed to meet UL 60950-1 and IEC 60950-1 requirements for supplementary insulation
- RoHS Compliant
- Operating Temperature -40°C to +85°C


Electrical Specifications @25°C	
Inductance	PIN 1-4 = 250uH $\pm$ 7% @ 10KHz/0.1V/Series (PIN 2-3 Short)
Leakage Inductance	PIN 1-4 = 1.1uH Max @ 1MHz/0.1V (PIN 2-3, PIN 7-8-9-10 Short)
Turn Ratio	PIN 1-4 : PIN 10-7 = 2.0 $\pm$ 2% : 1 (PIN2-3,PIN8-9 Short)
T.H.D.	PIN 1-4 to PIN 10-7= -86dB Max. @ 30KHz/3V (PIN 2-3,PIN 8-9 Short)
D.C.R.	PIN 1-4 = 1.50 ohm Max. (PIN2-3 short)
	PIN 10-7 = 1.25 ohm Max. (PIN8-9 short)
Hi-POT	PRI. – SEC. =1875VAC/60Hz/1Second/1mA

Dimensions

(Units: $\frac{\text{Inches}}{\text{mm}}$, Unless otherwise specified, all tolerances are $\pm \frac{.010}{0.25}$)



Schematic



Mark

1. Part Number----LAL0575
2. X----PRODUCT LINE or BLANK
3. DATE CODE----YYWW
4. SS----50 OR BLANK
5. G----RoHS

Package info

LAL0575-50R— Tape Reel